

AMENDMENTS TO CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A circular saw comprising:

a base with a table on a top of the base, a blade rotatably extending through a slot defined in the table, a first rail and a second rail located on two sides of the table, said first and second rails each having lower and upper surfaces, and

a rip guide having a lock handle pivotably connected to a first end thereof and a guide piece located at an underside of the lock handle, the guide piece having ~~rollers~~ at least one roller connected thereto which ~~contact an~~ contacts the upper surface of the first rail, a second end of the rip guide slidably engaged with the lower surface of the second rail.

2. (Original) The circular saw as claimed in claim 1, wherein the guide piece includes two through holes and each of the through holes has one roller engaged therewith.

3. (Currently Amended) ~~The~~ A circular saw ~~as claimed in claim 2~~ comprising:

a base with a table on a top of the base, a blade rotatably extending through a slot defined in the table, a first rail and a second rail located on two sides of the table, and

a rip guide having a lock handle pivotably connected to a first end thereof and a guide piece located at an underside of the lock handle, the guide piece having at least one roller connected thereto which contacts the upper surface of the first rail, a second end of the rip guide slidably engaged with the lower surface of the second rail,

wherein a rectangular retaining frame is connected to the guide piece and located in each of the through ~~hole~~ holes, and the roller ~~in~~ is rotatably enclosed by the retaining frame.

4. (Original) The circular saw as claimed in claim 2, wherein the roller in each of the through holes partially extends beyond a top surface of the guide piece.

5. (Original) The circular saw as claimed in claim 1, wherein the first rail includes a groove defined longitudinally in the upper surface thereof and the rip guide includes a protrusion which is slidably engaged with the groove.

6. (Original) The circular saw as claimed in claim 5, wherein the upper surface of the first rail includes a convex curve portion and an intermediate member is connected between the rip guide and the first rail, the intermediate member having the protrusion and a concave surface which is matched with the convex curve portion.

7. (Currently Amended) The circular saw as claimed in claim 1, wherein an end member is connected to a second end of the rip guide and includes an insertion which is inserted in an opening of the second end of the rip guide, an assist roller is connected to an underside of the insertion and ~~extending~~ extends beyond an opening defined in an underside of the second end of the rip guide, the assist roller ~~contacting~~ contacts a top surface of the second rail, and a hooking member is connected to the end member and slidably engaged with an underside of a dovetail-shaped ridge projecting from the second rail.